# STEELGREEN MANUFACTURING

# **SG36**



## **FEATURING**

#### O1 Standard Integrated 20/50 Amp Charging System

This powerful charging system gives you the ability to run a high-volume pump, foam markers, and other attachments.

#### O2 Oil Cooler

Reduces oil temperature, improves lubrication and extends oil change intervals.

#### **O3** Heavy-Duty Shift Solenoid Starter

Designed for long-lasting commercial use.

## **O4** Dual 15 Gal Spray Tanks

Hold up to 30 gallons of liquid. 15' spot spray coil hose is standard with 75' hose reel option available.

## **O5** High-Density Poly Fertilizer Tray

Two heavy-duty, lightweight trays add 100 lbs of granular product capacity.

#### **O6** Fertilizer Hopper

125-lb hydraulic-driven Spyker® granular system

## O7\* 21 HP Engine

Vanguard® commercial power 21 HP engine featuring V-Twin OHV Technology, Cooler Cleaner Technology (efficient fan and improved debris management), dynamically balanced crankshaft, and electronic ignition.

Honda® GXV660 21 HP engine is available as a custom option.

## **O8\*** Drum Parking Brakes

For brakes that hold (even on hills), our wheel motors have integrated drum brakes on both sides.

## **O9\*** Overfill Protection

Keeps fluid away from expensive electrical and hydraulic components.

#### **10\*** Tank Sump with Drain

Completely drain tanks without removing the hose.

#### 11\* Easy Access Nozzles

Stainless steel boom with hidden plumbing. Nozzles are easy to reach and change-no special tools required.

## **12\*** Donaldson® Air Cleaner

Donaldson® engine air filtration systems offer premium performance and protect and prolong the life of the engine.

#### 13\* 3 QT Oil Reservoir

High oil capacity for lower operating temperature.

#### 14\* Delavan® Pump

5-chamber positive displacement diaphragm pump with 12 VDC permanent magnet, totally enclosed motor.

Shurflo® diaphragm pump and Hypro high-volume roller pump are also available.

\* Pictured on reverse side

# FEATURES (CONT'D)



21 HP Engine



Drum Parking Brakes



Overfill Protection



Tank Sump with Drain



Easy Access Nozzles



Donaldson® Air Cleaner



3 QT Oil Reservoir



Delavan® Pump

# **SPECIFICATIONS**

• Spray Capacity: 30 gal

• **Spray Width:** 2' or 4' or 6' or 8'

• Hopper Capacity: 125 lbs

Variable Spread Width: up to 25'

• Fuel Capacity: 5 gal

• Transport Speed: 10 mph

• Rate Production: 120,000 sq. ft. per fill

based on ¼ gallon spray nozzles

# **DIMENSIONS**

Width: 35.5"

Length: 80"

Height: 54"

Front Tire: 16"

**Rear Tire:** 21x7.00-10