# STEELGREEN MANUFACTURING





## FEATURING

01	Standard Integrated 20/50 Amp Charging System
	This powerful charging system gives you the ability to run a
	high-volume pump, foam markers, and other attachments.

#### O2 Oil Cooler

Reduces oil temperature, improves lubrication and extends oil change intervals.

**O3** Heavy-Duty Shift Solenoid Starter Designed for long-lasting commercial use.

- O4 Dual 15 Gal Spray Tanks
  - Hold up to 30 gallons of liquid. Plus 75' hose reel comes standard.
- **O5** High-Density Poly Fertilizer Tray

Two heavy-duty, lightweight trays add 100 lbs of granular product capacity.

**O6** 22" Rear Wheels

22-inch commercial grade turf tires provide additional hillside stability and faster transport speeds.

**O7** Fertilizer Hopper

225-lb hydraulic-driven Spyker® granular system

**O8**\* 21 HP Engine

Vanguard<sup>®</sup> commercial power 21 HP engine featuring V-Twin OHV Technology, Cooler Cleaner Technology (efficient fan and improved debris management), dynamically balanced crankshaft, and electronic ignition.

Honda® GXV660 21 HP engine is available as a custom option.

#### **O9\*** Drum Parking Brakes

For brakes that hold (even on hills), our wheel motors have integrated drum brakes on both sides.

#### **10\*** Overfill Protection

Keeps fluid away from expensive electrical and hydraulic components.

#### **11\*** Tank Sump with Drain

Completely drain tanks without removing the hose.

#### 12\* Easy Access Nozzles

Stainless steel boom with hidden plumbing. Nozzles are easy to reach and change-no special tools required.

#### **13\*** Donaldson<sup>®</sup> Air Cleaner

 ${\sf Donaldson}^{\circledast}$  engine air filtration systems offer premium performance and protect and prolong the life of the engine.

### 14\* 3 QT Oil Reservoir

High oil capacity for lower operating temperature.

#### 15\* Delavan<sup>®</sup> Pump

5-chamber positive displacement diaphragm pump with 12 VDC permanent magnet, totally enclosed motor.

Shurflo $^{\otimes}$  diaphragm pump and Hypro $^{\otimes}$  high-volume roller pump are also available.

\* Pictured on reverse side

## FEATURES (CONT'D)



21 HP Engine



Drum Parking Brakes



Overfill Protection



Tank Sump with Drain



Easy Access Nozzles



Donaldson<sup>®</sup> Air Cleaner



3 QT Oil Reservoir



Delavan® Pump

## SPECIFICATIONS

- Spray Capacity: 30 gal
- Spray Width: 2' or 4' or 6' or 8'
- Hopper Capacity: 225 lbs
- Variable Spread Width: up to 25'
- Fuel Capacity: 5 gal
- Transport Speed: 12 mph
- **Rate Production:** 120,000 sq. ft. per fill based on ¼ gallon spray nozzles

# DIMENSIONS

Width: 46"

Length: 80"

Height: 54"

Weight: 950 lbs

Front Tire: 16"

Rear Tire: 22x11.00-10